



HEAVY BREAKERS	RX 26	RX 30	RX 38	RX 46	RX 54
Carrier weight Class t	20 – 33	25 – 40	29 – 46	35 – 55	45 – 70
Service weight kg	1,800	2,200	2,600	3,000	4,200
Tool diameter mm	140	150	155	165	180
Oil flow rate l/min	130 – 180	150 – 200	180 – 220	220 – 270	250 – 320
Operating pressure bar	150 – 170	150 – 170	160 – 180	160 – 180	160 – 180
Impact rate bpm (EasyPower)	400 – 800	450 – 800	530 – 800	540 – 800	550 – 800
Impact rate bpm (PowerStop)	380 – 650	380 – 620	380 – 590	380 – 580	380 – 570
Sound Power Level guaranteed dB(A)	122	122	124	124	126
Part Number without CP-Lube	3363 1123 91	3363 1124 31	3363 1126 03	3363 1138 76	3363 1138 38
Part Number with CP-Lube	3363 1168 13	3363 1168 14	3363 1168 15	3363 1168 16	3363 1168 17

COMPACTORS



Applications

- Used for slope, trench and waste compaction, road repair, side development and piling

Features

- Handle nearly every job with high compaction frequency and maximum vibrating force
- Models to fit most carriers and projects
- AutoLube system eliminates regular manual greasing
- No limitation of back pressure in the return line

COMPACTORS	RC 150	RC 350	RC 450	RC 850	RC 1050
Carrier weight class ¹⁾	1 – 3	3 – 8	4 – 9	9 – 20	20 – 40
Service weight ²⁾ kg	160	320	430	880	1,130
Height mm	486	623	622	764	786
Plate dimensions (W x L) mm	295 x 721	475 x 846	610 x 929	710 x 1,272	864 x 1,364
Plate coverage m ²	0.17	0.31	0.40	0.68	0.90
Vibrating force t	1.4	2.3	3.6	7.3	10.5
Vibrating frequency n/min	2,100	2,100	2,200	2,200	2,200
Operating pressure bar	150	150	150	150	150
Oil flow l/min	30	57	76	114	151
Motor oil quantity (in rotor housing) l	0.6	0.8	0.9	3.7	3.7
Part Number	1826 1018 07	1826 1018 08	1826 1018 09	1826 1018 10	1826 1018 11

¹⁾Weights apply to standard carriers only. Any variations must be agreed with Chicago Pneumatic and/or the carrier manufacturer prior to attachment.

²⁾Compactor with medium-sized adapter.

